

DID Video Wall Monitor 40VDW Display



ADVANTAGES

- Slim Bezel Width: 13(H) /13(V) mm
- Ideal for Digital Signage Application
 - Spread Single image across multiple monitors using Single video source
 - Perfectly Integrated with VuREX DID Manager
 - Remotely Controlled via TCP/IP network
 - RS-232C In & Out for Controlling the Monitors via Server / PC
- Flexibility
 - Vertical / Horizontal Display
 - Configure up to a 10 x 10
 - Various types of Mount Kits are available (Wall, Stand, Stand alone, Ceiling, Scissor)



VuREX VDW DID Video Walls possess all the excellent DID technology, multiple image processing technology, signal switching technology.

VuREX VDW DID Video Walls are suitable for a wide range of applications: Retail stores(Restaurants, Cinemas and Theaters), Public Venues(Airports, Railway Stations, Shopping Malls), as well as Entertainment and Events (Tradeshows, Conference Centers).

SPECIFICATIONS 40VDW


| | | | | | |
|--------------------|------------------------------|---------------------------------------|--------------------|-------------------------------|---|
| Display | Bezel Width | 13(H) /13(V) mm | Features | RS-232C Control | Serial Interface Control Program PC |
| | Active Display Area | 885.6 x 498.15 mm | | Filter Type | 3D Comb Filter |
| | Screen Size | 40" | | Deinterlacing | Yes |
| | Panel Resolution | 1920 x 1080 @60Hz | | Noise Reduction | Yes |
| | Pixel Pitch | 0.46125 x 0.46125 mm | | Multi Display Function | PIP / PBP / VOV(Video On Video) |
| | Brightness | 700cd/m ² | | Trigger Source Switching | Yes |
| | Contrast Ratio | 3,000 : 1 | | Auto Source Sequencing | Yes |
| | Viewing Angle (H/V) | 178° / 178° | | Auto Power Recovery | Yes |
| | Display Color | 16.7 Million | | Multi Language | English, Spanish, French, German, Italian |
| | Response Time (Gray to Gray) | < 8ms | | | |
| | Video System | NTSC / PAL | | | |
| Interface | Video In / Out (BNC Type) | 2 / 2 | Dimension | Outline Dimension (W x H x D) | 915 x 530 x 125 mm |
| | S-Video In | 1 | Net. Weight | 25Kg | |
| | VGA In (15Pin D-Sub) | 1 | Cabinet | Bezel Color / Cabinet Color | Black / Black |
| | Component In | 1 | | Case Material | Metal(Electronic galvanized Iron) |
| | HDMI In | 2 | Warranty | Part/Labor | 2year / 2year |
| | DVI In | 1 | | MTBF (Approx.) | 50,000 Hours |
| | Audio In (RCA Type) | 3(L+R) | Regulations | | NRTL, FCC, CE, RoHS |
| | PC Stereo In | 1 | | | |
| Transmitter | RS232C In / Out | 1 / 1 Monitor OSD Control Using PC | Power | Consumption : < On | < 220W |
| | Remote Control | Yes | | Power Source | AC100 ~ 240V (50 / 60Hz)) |
| Audio | Built-In Speaker | Yes (5W x 2) | Mount | VESA™ Mount Size | 400 x 200mm |
| | | | | Mount Kit | Optional (Wall, Stand, Stand alone, Ceiling, Scissor) |

LED Video Wall Monitor 40VDW Display

OTHER VIEW



FRONT VIEW




REAR VIEW



SIDE VIEW




DIMENSIONS



▲ FRONT VIEW



▲ SIDE VIEW



▲ REAR VIEW



▲ TOP VIEW

RN Electronics Co., Ltd

Add 414, 172, LS-ro, Gunpo-si, Gyeonggi-do, 435-824, Korea

Tel +82-70-4370-4459 Fax +82-31-624-2130 Email info@vurex.net Website www.vurex.net

RNElectronics